

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/646,979	08/22/2003	Ann Louise McCormack	KCX-1125 (19615)	1058
DORITY & MA	7590 11/21/200 ANNING, P.A.	EXAMINER		
P.O. BOX 1449			MATZEK, MATTHEW D	
GREENVILLE, SC 29602-1449			ART UNIT	PAPER NUMBER
			1794	
			MAIL DATE	DELIVERY MODE
			11/21/2007	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

	Application No.	Applicant(s)				
Office Action Summary	10/646,979	MCCORMACK ET AL.				
omec Action Gummary	Examiner	Art Unit				
The MAII ING DATE of this communication ann	Matthew D. Matzek	orrespondence address				
The MAILING DATE of this communication appears on the cover sheet with the correspondence address Period for Reply						
A SHORTENED STATUTORY PERIOD FOR REPLY WHICHEVER IS LONGER, FROM THE MAILING DA - Extensions of time may be available under the provisions of 37 CFR 1.13 after SIX (6) MONTHS from the mailing date of this communication. - If NO period for reply is specified above, the maximum statutory period w - Failure to reply within the set or extended period for reply will, by statute, Any reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).	ATE OF THIS COMMUNICATION 36(a). In no event, however, may a reply be tim will apply and will expire SIX (6) MONTHS from cause the application to become ABANDONE!	J. nely filed the mailing date of this communication. D (35 U.S.C. § 133).				
Status						
1) Responsive to communication(s) filed on 11 Se	Responsive to communication(s) filed on <u>11 September 2007</u> .					
· <u> </u>	, _					
•	Since this application is in condition for allowance except for formal matters, prosecution as to the merits is					
closed in accordance with the practice under Ex parte Quayle, 1935 C.D. 11, 453 O.G. 213.						
Disposition of Claims						
4)⊠ Claim(s) <u>1-30</u> is/are pending in the application.						
4a) Of the above claim(s) <u>28-30</u> is/are withdrawn from consideration.						
5) Claim(s) is/are allowed.						
	Claim(s) <u>1-27</u> is/are rejected.					
7) Claim(s) is/are objected to. 8) Claim(s) are subject to restriction and/or	r election requirement					
o) Callin(s) are subject to restriction and/or election requirement.						
Application Papers						
9)☐ The specification is objected to by the Examiner.						
10) \square The drawing(s) filed on <u>22 August 2003</u> is/are: a) \square accepted or b) \square objected to by the Examiner.						
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).						
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d). 11) The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.						
Priority under 35 U.S.C. § 119						
12) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).						
a) ☐ All b) ☐ Some * c) ☐ None of:						
 1. Certified copies of the priority documents have been received. 2. Certified copies of the priority documents have been received in Application No 						
3. Copies of the certified copies of the priority documents have been received in this National Stage						
application from the International Bureau (PCT Rule 17.2(a)).						
* See the attached detailed Office action for a list of the certified copies not received.						
Attachment(s)						
1) Notice of References Cited (PTO-892) 4) Interview Summary (PTO-413)						
2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948) Paper No(s)/Mail Date 3) ☐ Information Disclosure Statement(s) (PTO/SB/08) Notice of Informal Patent Application						
Paper No(s)/Mail Date 6) Other:						

Art Unit: 1794

Continued Examination Under 37 CFR 1.114

1. A request for continued examination under 37 CFR 1.114, including the fee set forth in 37 CFR 1.17(e), was filed in this application after final rejection. Since this application is eligible for continued examination under 37 CFR 1.114, and the fee set forth in 37 CFR 1.17(e) has been timely paid, the finality of the previous Office action has been withdrawn pursuant to 37 CFR 1.114. Applicant's submission filed on 9/11/2007 has been entered.

Response to Amendment

2. The amendment dated 9/11/2007 has been fully considered and entered into the Record. Claim 1 has been amended, but contains no new matter. Claims 1-30 are currently pending. Claims 28-30 have been withdrawn from consideration. Claims 1-27 are currently active. The previous prior art rejections based upon Heyn et al. and Haffner et al. have been withdrawn as the prior art of Record fails to provide for the new claim limitation of having the discrete regions of carrier resin phase completely intermixed with and surrounded by the letdown resin phase.

Terminal Disclaimer

3. The terminal disclaimer filed on 9/11/2007 disclaiming the terminal portion of any patent granted on this application, which would extend beyond the expiration date of applications 10/703,761 and 10/918,553 have been reviewed and is accepted. The terminal disclaimer has been recorded. Therefore, the previous obvious double patenting rejections made in view of the aforementioned applications have been withdrawn.

Claim Rejections - 35 USC § 103

The text of those sections of Title 35, U.S. Code not included in this action can be found in a prior Office action.

Art Unit: 1794

4. Claims 1-5 and 7-27 are rejected under 35 U.S.C. 103(a) as being unpatentable over Heyn et al. (US 6,106,956) in view of Haffner et al. (US 6,045,900) and Norquist et al. (US 6,447,875 B1).

Heyn et al. teach a polymeric film comprising at least a first and second a. contiguous and coextruded portions, wherein the first portion contains filler to increase its water vapor permeability and the second portion serves to improve the tensile strength of the film (Abstract). The first portion (carrier resin) of the film may be made of linear low-density polyethylene copolymer (LLDPE) (col. 2, lines 52-67). It is preferred that the carrier resin contains 65 weight percent or less filler (col. 3, lines 60-65). The second portion (letdown resin) may be made of the same or different polyolefins and as with the first resin the preferred composition is LLDPE. The second portion preferably contains no filler (col. 4, lines 26-39). The LLDPE used in this film is to have a density of about 0.900 to about 0.935g/cm³ and a melt index of about 0.1 to about 5.0 grams per 10 minutes (col. 3, lines 10-15). The applied film meets the instantly claimed moisture vapor transmission rates (col. 6, lines 49-56) for diaper backsheets. The applied reference is silent as to the use of a nonwoven support layer to be bonded to the oriented film. Instant claim 1 requires different ethylene copolymers with a density difference of at least 0.003 g/cc between the carrier and letdown resins. Heyn et al. provide this for in that densities of the ethylene copolymers may vary from 0.900 to about 0.935g/cm³ and that the same or different copolymers may be used in the separate phases. As stated in the abstract the polymers used in each phase have different physical properties in order for separation to occur between the two phases. Heyn et al. fail to teach or suggest

Art Unit: 1794

having the discrete regions of carrier resin phase completely intermixed with and surrounded by the letdown resin phase.

- b. Haffner et al. teach a breathable barrier comprising a film layer comprising a filled film comprising about 50 to 70% calcium carbonate (col. 8, lines 23-25) and ethylene polymer (Abstract) and another layer comprising a nonwoven, spunbonded or bonded carded web layer (col. 3, lines 50-52). The laminate has a WVTR (MVTR) of more than 1500 g/m²/day (col. 3, lines 34-37). Example 1 teaches the use of calcium carbonate (filler), LLDPE [carrier resin] (density of 0.918 g/cm³ and a melt index of 3.5 g/10 min) and a LDPE [letdown resin] (density of 0.916 g/cm³ and a melt index of 12 g/10 min). Examiner takes the position that the filler is necessarily contained within the carrier resin phase as the filler is mixed with the carrier resin and then formed into a layer. Haffner et al. teach the blending of LLDPE with densities desirably ranging from 0.86-0.88 g/m³ with a second polyethylene ranging from 0.90 to 0.95 g/m³ (col. 9, lines 1-5 and col. 10, lines 1-11) to form an intermediate layer that may also contain filler that is similar in type and content to that of the breathable layer (col. 10, lines 48-58). This provides for density differences of up to 0.09 g/cm³.
- c. The basis weight of the film layer desirable ranges from 15-35 g/m 2 (col. 10, lines 59-64). An extensive list of ethylene (polyolefin) polymers has been disclosed including linear low-density polyethylene (LLDPE) (col. 7, line 49 col. 8, line 8). The nonwoven layer may comprise spunbonded and bonded carded webs (col. 3, lines 46-52).
- d. Claims 17 and 18 are rejected as the nonwoven woven layer may comprise multilayer nonwoven laminates (col. 11, lines 4-10). Claims 19 and 20 are rejected as the

Art Unit: 1794

film layer may comprise multiple layers **12** (Fig. 1). Haffner et al. teach a WVTR in excess of 1500 g/m²/day. This anticipates the breathability of instant claim 23. Claim 25 is rejected as the base layer **14** comprises from about 50% to about 98% of the multilayer film thickness (col. 10, lines 66-67). Claims 26 and 27 are rejected as the breathable barrier of Haffner et al. may be used in garments and personal care products (col. 1, lines 14-17).

- e. It is noted herein that the teachings of Haffner et al. include WVTR in excess of 1500 g/m²/day. It is the Examiner's interpretation that such a teaching encompasses the ranges of 5,000 and 10,000 g/m²/day as claimed herein. The use of material with high WVTR is recognized in the art of breathable barriers as it is evidenced herein by Haffner et al. The larger the WVTR value the greater the ability for the article to allow water vapor to be expelled from the article. This is highly desirable as the article is intentionally created for its breathability.
- f. Since Heyn et al. and Haffner et al. are from the same field of endeavor (i.e. filler filled LLDPE films), the purpose disclosed by Haffner et al. would have been recognized in the pertinent art of Heyn et al.
- g. It would have been obvious at the time the invention was made to a person having ordinary skill in the art to have bonded the film of Heyn et al. to the support layer of Haffner et al. as well as make the article according to the basis weights and density and melt flow index differences of Haffner et al. The skill artisan would have been motivated by the desire to create a breathable article that is capable of being used in personal absorbent articles.

Art Unit: 1794

h. Norquist et al. disclose a die apparatus that allows for the production of coextruded polymeric articles with a plurality of distinct, discontinuous phases located
within a surrounding matrix (abstract and Figure 4). Polyolefins may be used in the
creation of the co-extruded article, for example the embedded phase may comprise
polyethylene and the surrounding matrix may comprise polypropylene (claim 4). Various
additives may be incorporated into the embedded phase to modify the properties of the
finished web (col. 11, lines 56-60). Co-extruded webs formed using the apparatus and
method of the invention are also suitable for use in various medical articles. In certain
embodiments, phases are formed in the web matrix in order to provide increased strength
and improved handling without affecting the overall conformability, transparency or
breathability of the polymeric material. A preferred web matrix material for use in
constructing such medical articles is polyethylene and a preferred embedded phase
material is also polyethylene (col. 14, lines 48-65).

- i. Since Heyn et al. and Norquist et al. are from the same field of endeavor (i.e. co-extruded polymeric films), the purpose disclosed by Norquist et al. would have been recognized in the pertinent art of Heyn et al.
- j. It would have been obvious at the time the invention was made to a person having ordinary skill in the art to have made the co-extruded film of Heyn et al. in the manner set forth in Norquist et al. The skill artisan would have been motivated by the desire to provide the co-extruded film of Heyn et al. with increased strength and improved handling without affecting the overall conformability, transparency or breathability of the polymeric material (col. 14, lines 47-55).

Art Unit: 1794

3. Claim 6 is rejected under 35 U.S.C. 103(a) as being unpatentable over Heyn et al. (US 6,106,956) in view of Haffner et al. (US 6,045,900) and Norquist et al. (US 6,447,875 B1) as applied to claim 1 above, and further in view of Bansal (US 2003/017054 A1). The inventions of Heyn et al., Haffner et al. and Norquist et al. are silent as to the use of an ethylene with a melt index of at least 20g/10min.

- a. Bansal discloses a multiple component spunbonded web and laminates thereof comprising a LLDPE core component (abstract) that has a density between 0.91 and 0.95 g/cc and a melt index between 18g/10min to 22 g/10min [0013].
- b. Since Heyn et al. and Bansal are from the same field of endeavor (i.e. co-extruded polymers), the purpose disclosed by Bansal would have been recognized in the pertinent art of Heyn et al.
- c. It would have been obvious at the time the invention was made to a person having ordinary skill in the art to have made the co-extruded film of Heyn et al. having the carrier resin being a polyethylene with a melt index of at least about 20 g/10 min. The skill artisan would have been motivated by the desire to create a product with superior grab tensile strength and minimized surface fuzzing [0026].

Response to Arguments

4. Applicant's arguments with respect to claims 1-27 have been considered but are moot in view of the new ground(s) of rejection.

Art Unit: 1794

Conclusion

Any inquiry concerning this communication or earlier communications from the

examiner should be directed to Matthew D. Matzek whose telephone number is 571.272.2423.

The examiner can normally be reached on M-F, 9-5:30.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's

supervisor, Terrel Morris can be reached on 571.272.1478. The fax phone number for the

organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent

Application Information Retrieval (PAIR) system. Status information for published applications

may be obtained from either Private PAIR or Public PAIR. Status information for unpublished

applications is available through Private PAIR only. For more information about the PAIR

system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR

system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would

like assistance from a USPTO Customer Service Representative or access to the automated

information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/Matthew D Matzek/

Examiner, Art Unit 1794

/Norca L. Torres-Velazquez/ Primary Examiner, Art Unit 1794.